

PRODUCT-DETAILS

# OT400E04CP

## OT400E04CP CHANGE-OVER SWITCH



### General Information

Extended Product Type	OT400E04CP
Product ID	1SCA022771R8680
EAN	6417019251967
Catalog Description	OT400E04CP CHANGE-OVER SWITCH
Long Description	Including a black plastic IP65 I-0-II pistol type handle (see the table below), shaft and bolt set for the cable connection. Handle padlockable in the 0-position, door interlock in the I- and lipositions and when padlocked.

### Popular Downloads

Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC301041M0002

### Dimensions

Product Net Width	265 mm
Product Net Height	185 mm
Product Net Depth / Length	203 mm
Product Net Weight	7.415 kg 16.35 lb

## Technical

Rated Operational Current AC-21A ( $I_e$ )	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Current AC-22A ( $I_e$ )	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Current AC-23A ( $I_e$ )	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Current AC-31B ( $I_e$ )	(380 ... 415 V) 400 A
Rated Operational Current AC-33B ( $I_e$ )	(380 ... 415 V) 400 A
Rated Operational Power AC-23A ( $P_e$ )	(380 ... 415 V) 220 kW (500 V) 280 kW (690 V) 400 kW
Conventional Free-air Thermal Current ( $I_{th}$ )	$q = 40\text{ °C}$ 400 A
Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 400 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	12 kV
Rated Insulation Voltage ( $U_i$ )	1000 V
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current ( $I_{cw}$ )	for 1 s 15 kiloampere rms
Power Loss	10 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft included
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - Simultaneous Function
Switches Operating Mechanism	Mechanism at the End of the Switch 04 (Left Side)
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	4
Degree of Protection	Front IP20
Terminal Width	25 mm
Tightening Torque	acc. IEC 60947-1 30 ... 44 N·m

## Environmental

Environmental Information	1SCC303050D0201
---------------------------	-----------------

## Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SCC303005D0202
Environmental Information	1SCC303050D0201
Instructions and	1SCC301041M0002

Manuals

RoHS Information	1SCC301149D0202
------------------	-----------------

**Container Information**

Package Level 1 Units	1 piece
Package Level 1 Width	240 mm 9.45 in
Package Level 1 Depth / Length	325 mm 12.8 in
Package Level 1 Height	218 mm 8.58 in
Package Level 1 Gross Weight	7.865 kg 17.34 lb
Package Level 1 EAN	6417019251967

**Classifications**

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

**Categories**

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Manual Change-over Switches

