

PRODUCT-DETAILS

SJ203-C40

Miniature Circuit Breaker - SJ200 - 3P - C - 40 ampere



General Information

Extended Product Type	SJ203-C40
Product ID	2TAZ141300R0404
EAN	6957625328733
Catalog Description	Miniature Circuit Breaker - SJ200 - 3P - C - 40 ampere
Long Description	Miniature Circuit Breaker SJ203-C40

Technical

Standards	IEC/EN 60898-1 GB 10963
Number of Poles	3
Number of Protected Poles	3
Tripping Characteristic	C
Rated Current (I_n)	40 A
Rated Operational Voltage	400 V AC
Rated Insulation Voltage (U_i)	440 V
Rated Short-Circuit Capacity (I_{cn})	(400 V) 6 kA
Energy Limiting Class	3
Oversvoltage Category	III
Pollution Degree	2
Rated Impulse	4 kV

Withstand Voltage (U_{imp})

Degree of Protection	IP20
Connecting Capacity	Rigid 0 ... 25 mm ² Flexible 0 ... 25 mm ²
Built-In Depth (t_2)	69 mm

Environmental

Ambient Air Temperature	Operation -25...55 °C
-------------------------	-----------------------

Dimensions

Product Net Width	0.053 m
Product Net Depth / Length	0.044 m
Product Net Height	0.088 m
Product Net Weight	0.286 kg

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85362010

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	No declaration needed
Instructions and Manuals	No document available

Popular Downloads

Data Sheet, Technical Information	1SXF400005C2013
Instructions and Manuals	No document available

Classifications

ETIM 6	EC000042 - Miniature circuit breaker (MCB)
ETIM 7	EC000042 - Miniature circuit breaker (MCB)

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs

