

PRODUCT DATASHEET

DST STICK 23 W/865 220...240 V E27

OSRAM DULUXSTAR STICK | Compact fluorescent integrated, stick shape



AREAS OF APPLICATION

- General illumination
- Domestic applications
- Wherever compact and efficient lamps are needed
- Wherever cold light colors are needed
- Outdoor use in enclosed and ventilated luminaires only

PRODUCT BENEFITS

- Fast return on investment
- Up to 80 % less energy consumption compared with ordinary light bulbs

PRODUCT FEATURES

- Available in 2 light colors: 827 and 865
- Also available in activating light color LUMILUX Cool Daylight
- Average life: up to 8,000 h



TECHNICAL DATA

Electrical data

Rated wattage	23.00 W
Nominal voltage	220...240 V
Claimed equiv. conventional lamp power	100 W
Nominal wattage	23.00 W
Power factor λ	≥ 0.50
Nominal current	0.23 A
Operating frequency	50...60 Hz


Photometrical data

Nominal luminous flux	1330 lm
Rated luminous flux	1330 lm
Rated color temperature	6500 K
Light color	865
Light color (designation)	Daylight
Color temperature	6500 K
Luminous flux	1330 lm
Color rendering index Ra	≥ 80

Light technical data

Warm-up time (60 %)	≤ 60.00 s
Starting time	≤ 2.0 s

Dimensions & weight



Maximum diameter	48.0 mm
Overall length	176.0 mm
Product weight	85.00 g
Length	176.0 mm

Lifespan

Nominal lamp life time	6000 h
Rated lamp life time	6000 h
Number of switching cycles	4000

Additional product data

Base (standard designation)	E27
Mercury content	2.0 mg
Show WEEE picto	Yes

Capabilities

Dimmable	No
----------	----


Certificates & standards

Cleaning instruction in case of breakage	What to do if a lamp containing mercury breaks?
------------------------------------------	-------------------------------------------------

Country-specific categorizations

ILCOS	FBT-23/65/1B-220/240-E27
-------	--------------------------

Light Distribution



Spectral power distribution

SAFETY ADVICE

In case of lamp breakage: www.ledvance.com/brokenlamp
Not for use with external dimmers or electronic switches.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300796147	Folding carton box 1	52 mm x 52 mm x 178 mm	0.11 g	0.48 dm ³
4008321873620	Shipping carton box 20	268 mm x 216 mm x 193 mm	2.46 g	11.17 dm ³
4050300940243	Folding carton box 1	50 mm x 50 mm x 178 mm	94.00 g	0.45 dm ³
4050300940250	Shipping carton box 10	261 mm x 109 mm x 194 mm	1022.00 g	5.52 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.